


Go Basics

WASA: Web and Software Architecture

Prof. Emanuele Panizzi

GO Language



The banner features the Go logo (a stylized 'GO' with a blue 'G' and white 'O') in the top left corner. Below it, the text reads "Build fast, reliable, and efficient software at scale". To the right of the text is a cartoon blue creature with a white horn and a red nose, climbing a white ladder. On the left side, there are four bullet points with checkmarks:

- ✓ Go is an open source programming language supported by Google
- ✓ Easy to learn and get started with
- ✓ Built-in concurrency and a robust standard library
- ✓ Growing ecosystem of partners, communities, and tools




Figure 1: Companies using Go

Go Playground



Figure 2: <https://go.dev/play/>

Packages

- Go functions are grouped into packages.
- Each package is made of one or more files in the same directory
- The package is declared at the beginning of the file, e.g.: `package main` below

```
package main
```

```
//...
```

Import

- A file can import other packages, e.g.:

```
import (  
    "fmt"  
    "math/rand"  
)
```

Hello World

- Let's import the `fmt` package, which contains functions for formatting and printing text

```
package main

import "fmt"

func main() {
    fmt.Println("Hello, world!")
}
```

- You can use the functions of the imported package if their name begins with a capital letter
- same for variables (e.g., `math.Pi`)

Go basic types

`bool`

`string`

`int int8 int16 int32 int64`

`uint uint8 uint16 uint32 uint64 uintptr`

`byte // alias for uint8`

`rune // alias for int32, represents a Unicode code point`

`float32 float64`

`complex64 complex128`

Variables

```
package main
import "fmt"

// these are visible in the package
var b bool
var s string
var x, y float32

func main() {
    var i int // this is local in this function
    fmt.Println(i, b, s, x, y)
}
```

- Note that type is after the variable name(s)

Initial values

```
var i int = 10
var b = true // takes the type of the initializer
var x, y = 1.5, 2.5
```

Zero values are used when there is no explicit initial value:

- 0 for numeric types,
- false for the boolean type, and
- "" (the empty string) for strings.

Short declaration with initialization inside functions

```
package main
import "fmt"

func main() {
    k := 3
    fmt.Println(k)
}
```

Constants

```
// ...  
const k = 10  
const zero = -273.15  
// ...
```

Arrays

```
package main
import "fmt"

func main() {
    var v [10]int
    odds := [5]int{1, 3, 5, 7, 9}
    i := 4
    v[0] = odds[i] // 9
    fmt.Println(v)
}
//[9 0 0 0 0 0 0 0 0 0]
```

Slices

```
package main
import "fmt"

func main() {
    vowels := [5]string{"a","e","i","o","u"}
    var s []string = vowels[1:3] // [e, i] (half-open range)
    fmt.Println(s)
}
```

- default is zero for the slice's low bound and the length of the array for the high bound
- `vowels[0:5]`, `vowels[:5]`, `vowels[0:]`, and `vowels[:]` are the same

Slices (contd)

- A slice does not store any data, it just describes a section of an underlying array.

```
package main
import "fmt"

func main() {
    vowels := [5]string{"a","e","i","o","u"}
    var s []string = vowels[1:3]
    t := vowels[1:3]
    fmt.Println(t) // [e i]
    s[0] = "x"
    fmt.Println(vowels) // [a x i o u]
    fmt.Println(t) // [x i]
}
```

- Array Literal

```
[3]bool{true, true, false}
```

- Slice Literal

```
[]bool{true, true, false}
```

it creates an array and then a slice that references it

Slices (contd)

- length: number of elements in the slice
- capacity: number of elements from low bound to end of array
- e.g.: `var s []string = vowels[1:3]`: `len(s) = 3`, `cap(s) = 4`
- builtin `make()` function:

```
package main
```

```
import "fmt"
```

```
func main() {
```

```
    b := make([]int, 0, 5)
```

```
    fmt.Println(len(b)) // 0
```

```
    fmt.Println(cap(b)) // 5
```

```
    fmt.Println(b) // [] or nil
```

```
}
```


Maps

```
package main
import "fmt"

var temperatures map[string]int

func main() {
    temperatures = make(map[string]int)
    // must use make() to initialize a map
    temperatures["Rome"] = 27
    temperatures["London"] = 18
    temperatures["San Francisco"] = 21
    fmt.Println(temperatures)
}
```

Maps (contd)

```
package main
import "fmt"

func main() {
    // with map literals
    var temp = map[string]int{
        "r": 27,
        "l": 18,
        "s": 21,
    }
    fmt.Println(temp) // map[l:18 r:27 s:21]
}
```

Maps (contd)

- `delete(m, key)` to delete an element
- e.g. `delete(temperatures, "Rome")`
- `elem, ok := m[key]` to test that a key is present
- e.g.

```
//...
```

```
elem, ok := temperatures["London"] // 18 true
```

```
elem, ok = temperatures["Paris"] // 0 false
```

```
//...
```

- (this is two-value assignment)

Pointers

- The type `*T` is a pointer to a `T` value. Its zero value is `nil`.
- e.g., `var p *int`
- The `&` operator generates a pointer to its operand, e.g.:

```
i := 42  
p = &i
```

- Dereferencing

```
fmt.Println(*p) // read i through the pointer p  
*p = 21         // set i through the pointer p
```